

## Fernfühlerkurven:

Gespeichert in: ATR 4800 / ATR 4800-16 /  
UTE 2800-F / UTE 2800-L / UTE 3800-U

# EBERLE

Description					Pt No 000 19 3720 001 [F 193 720, Length 4 m, extendable up to 50 m]
NTC Type	NTC 2K	NTC 10K	NTC12K	NTC 15K	NTC 33K
°C	Ohm (typ)	Ohm (typ)	Ohm (typ)	Ohm (typ)	Ohm (typ)
-30	24651	142299	206422	213449	711711
-25	18902	106473	151286	159710	516153
-20	14615	80585	112246	120878	378378
-15	11391	61653	84250	92480	278883
-10	8947	47652	63929	71478	207659
-5	7079	37185	49012	55778	155354
0	5642	29282	37942	43924	117358
5	4527	23258	29645	34887	89493
10	3657	18624	23364	27936	68838
15	2973	15028	18567	22543	53473
20	2431	12216	14871	18325	41854
25	2000	10000	12000	15000	33000
30	1654	8239	9752	12359	26209
35	1376	6832	7978	10248	20878
40	1151	5698	6569	8548	16744
45	967	4780	5442	7171	13539
50	816	3860	4535	6048	11010
55	693	3419	3800	5128	8990
60	590	2913	3201	4370	7382
65	505	2494	2710	3741	6091
70	434	2145	2306	3217	5051
75	374	1852	1971	2779	4209
80	324	1606	1692	2410	3523
85	282	1399	1459	2098	2968
90	246	1223	1263	1834	2510
95	215	1073	1098	1609	2129
100	189	944	958	1417	1813
105	167	834	839	1251	1551
110	147	739	737	1109	1332
115	130	657	650	986	1147
120	116	586	574	879	990