

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.02.2021

Version: 8.00

Revision: 06.08.2019

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** SONAX SX 90 PLUS**Article number:**

04745050, 04747050, 04749000

**UFI:** SEJ3-20DV-G00N-HDY7**1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category PC24** Lubricants, greases, release products**Application of the substance / the mixture**

Penetrating oil

Anticorrosion additive

Lubricant

**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

**Further information obtainable from:**

Product safety

E-mail: [erp@sonax.de](mailto:erp@sonax.de)

Phone: + 49 (0) 8431 53 217

**United Kingdom:**

Saxon

Everland Road,

Hungerford, Berkshire, RG17 0DX, UK

Tel: 01488 689 400 | Fax: 01488 684317

e-mail: [info@saxon-brands.com](mailto:info@saxon-brands.com)**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Eye Irrit. 2 H319 Causes serious eye irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS07 GHS08

**Signal word** Danger**Hazard-determining components of labelling:**

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics

White mineral oil, petroleum

**Hazard statements**

H319 Causes serious eye irritation.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2021

Version: 8.00

Revision: 06.08.2019

**Trade name: SONAX SX 90 PLUS**

(Contd. of page 1)

### Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P280 Wear eye protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P331 Do NOT induce vomiting.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Formulation of mineral oil with additives in petroleum distillate

#### Dangerous components:

EC No 926-141-6 Reg.nr.: 01-2119456620-43-xxxx	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304	25-<50%
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27-xxxx	White mineral oil, petroleum ⚠ Asp. Tox. 1, H304	25-<50%
CAS: 1474044-79-5 EC No 939-717-7 Reg.nr.: 01-2119980985-16-xxxx	calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) Alternative CAS number: 57855-77-3 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-<3%
CAS: 110-25-8 EINECS: 203-749-3 Reg.nr.: 01-2119488991-20-xxxx	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Aquatic Chronic 3, H412	1-<3%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46-xxxx	2,6-di-tert-butyl-p-cresol ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410	<0.25%

#### Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons	≥30%
------------------------	------

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information:

Take affected persons out into the fresh air.

Remove soiled clothing

#### After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

#### After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

#### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)

**Trade name: SONAX SX 90 PLUS**

(Contd. of page 2)

**4.2 Most important symptoms and effects, both acute and delayed**

Eye irritation  
Coughing  
Breathing difficulty  
Headache  
Nausea  
Unconsciousness  
Reddening, drying and crack formation of the skin

**4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed or in case of vomiting, danger of entering the lungs.  
Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:**

Water haze  
Foam  
Fire-extinguishing powder  
Carbon dioxide

**5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)  
Carbon dioxide (CO<sub>2</sub>)  
Phosphorus oxides (e.g. P<sub>2</sub>O<sub>5</sub>)

**5.3 Advice for firefighters****Protective equipment:**

Do not inhale explosion gases or combustion gases.  
Wear fully protective suit.  
Do not enter the hazardous area without a self-contained breathing apparatus.  
See Section 8 for information on personal protection equipment.

**Additional information**

Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.  
Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
When using product on electrical parts disconnect them from power supply first. Before re-assembly, let dry for 2 minutes.

**Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2021

Version: 8.00

Revision: 06.08.2019

Trade name: SONAX SX 90 PLUS

(Contd. of page 3)

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

**Requirements to be met by storerooms and receptacles:** Provide solvent resistant, sealed floor.

**Information about storage in one common storage facility:** Store away from foodstuffs.

#### Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Recommended storage temperature: 20 °C.

### 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

##### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

RCP-TWA (EU)	Long-term value: 1200 mg/m <sup>3</sup> , 165 ppm Vapour / Total Hydrocarbons
--------------	--

##### CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

WEL (Great Britain)	Long-term value: 10 mg/m <sup>3</sup>
---------------------	---------------------------------------

Regulatory information WEL (Great Britain): EH40/2018

#### DNELs

##### CAS: 8042-47-5 White mineral oil, petroleum

Oral	DNEL	40 mg/kg (consumer) (long-term exposure - systemic effects)
Dermal	DNEL	92 mg/kg bw/day (consumer) (long-term exposure - systemic effects)
		220 mg/kg bw/day (worker) (long-term exposure - systemic effects)
Inhalative	DNEL	35 mg/m <sup>3</sup> (consumer) (long-term exposure - systemic effects)
	DNEL	160 mg/m <sup>3</sup> (worker) (long-term exposure - systemic effects)

##### CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)

Dermal	DNEL	10 mg/kg bw/day (worker) (longterm systematic effects)
Inhalative	DNEL	5 mg/m <sup>3</sup> (vls) (longterm systematic effects)

##### CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

Dermal	DNEL	5 mg/kg (VL)
		8.3 mg/kg (worker)
Inhalative	DNEL	1.74 mg/m <sup>3</sup> (VL)
		5.8 mg/m <sup>3</sup> (worker)

#### PNECs

##### CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)

PNEC	10 mg/l (sewage plant)
	0.004 mg/l (freshwater (Süßwasser))
	0.0004 mg/l (water (sea water))
PNEC	69 mg/kg (sediment (fresh water))
	6.9 mg/kg (sediment (sea water))
	13.9 mg/kg (soil)

##### CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

Oral	PNEC	16.7 mg/kg food (human)
	PNEC	100 mg/l (sewage plant)
		0.004 mg/l (sporadic release)
		0.004 mg/l (freshwater (Süßwasser))
PNEC	0.0004 mg/l (sediment (sea water))	
	1.29 mg/kg (sediment (fresh water))	
		1.04 mg/kg (soil)

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.02.2021

Version: 8.00

Revision: 06.08.2019

Trade name: SONAX SX 90 PLUS

(Contd. of page 4)

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls****Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

**Personal protective equipment:****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

**Respiratory protection:**

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

**Protection of hands:** Protective gloves

**Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

[EN 374]

**Penetration time of glove material** Value for the permeation: Level 6 ( $\geq 480$ min)

**Eye protection:**

Safety glasses

[EN 166]

## SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	brown-opaque
<b>Odour:</b>	Solvent-like
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not applicable.

**Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	180 - 270 °C

**Flash point:** 85 °C (DIN 51758)

**Flammability (solid, gas):** Not applicable.

**Decomposition temperature:** Not determined.

**Auto-ignition temperature:** Not determined.

**Explosive properties:** Not determined.

**Explosion limits:**

<b>Lower:</b>	0.6 Vol.% (Main ingredient data)
<b>Upper:</b>	7.0 Vol.% (Main ingredient data)

**Vapour pressure:** Not determined.

<b>Density at 20 °C:</b>	0.84 - 0.85 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not applicable.

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.02.2021

Version: 8.00

Revision: 06.08.2019

Trade name: SONAX SX 90 PLUS

(Contd. of page 5)

**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Partition coefficient: n-octanol/water:**

Not determined.

**Viscosity:**

**Flow time at 23 °C**

40-50 s (DIN EN ISO 2431/3mm)

**Kinematic at 40 °C:**

<20.5 mm<sup>2</sup>/s (DIN 51562)

**9.2 Other information**

No further relevant information available.

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No dangerous reactions known.

**10.2 Chemical stability** Stable under normal conditions.

**10.3 Possibility of hazardous reactions** No dangerous reactions known.

**10.4 Conditions to avoid**

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

**10.5 Incompatible materials:** strong oxidizing agents

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

**11.1 Information on toxicological effects** There are no toxicological findings on this mixture.

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5,000 mg/m <sup>3</sup> (rat) (OECD 403)

**CAS: 8042-47-5 White mineral oil, petroleum**

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4d	>5,000 mg/l (rat)

**CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)**

Oral	LD50	>2,500 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50	>9,000 mg/l (rat)

**CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine**

Oral	LD50	5,000 mg/kg (rat)
Inhalative	LC50/4d	1.37 mg/l (rat)

**CAS: 128-37-0 2,6-di-tert-butyl-p-cresol**

Oral	LD50	>5,000 mg/kg (rat) (OECD-Prüfrichtlinie 401)
Dermal	LD50	>5,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)

**Primary irritant effect:**

**Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

Long-term exposure causes slight irritation of the skin.

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Repeated dose toxicity**

Based on available data, the classification criteria are not met.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.02.2021

Version: 8.00

Revision: 06.08.2019

Trade name: SONAX SX 90 PLUS

(Contd. of page 6)

**CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)**

Dermal | NOAL 90 d | 100 mg/kg (rat) (OECD 408, 90d, target organ: liver)

**CAS: 128-37-0 2,6-di-tert-butyl-p-cresol**

Oral | NOAEL | 25 mg/kg (Ratte)

**CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard**Viscosity: < 20,5mm<sup>2</sup>/s (40°C)

May be fatal if swallowed and enters airways.

**SECTION 12: Ecological information****12.1 Toxicity** There are no ecotoxicological data available on this mixture.**Aquatic toxicity:****Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
ELO 48 h	1,000 mg/l (Daphnia magna)
ELO 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)

**CAS: 8042-47-5 White mineral oil, petroleum**

LC50 / 96h	>100 mg/l (fish)
EC50 / 48h	>100 mg/l (daphnia)
NOEC/NOEL	≥100 mg/l (fish) (96h)
	≥100 mg/l (algae) (72h)
	≥100 mg/l (daphnia) (48h)

**CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)**

NOEL 21 d	2.2-10 mg/l (daphnia)
LC50 / 96h	>0.28 mg/l (fish)
EC50 / 48h	>0.27 mg/l (Daphnia magna)
NOEC / 72 h	>0.27 mg/l (algae)

**CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine**

LC50 / 96h	3.2-4.6 mg/l (fish)
EC0 / 72 h	>20 mg/l (algae)
EC20 / 0.5 h	50 mg/l (activated sludge)
EC50 / 48h	0.53 mg/l (Daphnia magna)
EC50 / 72h	5.1 mg/l (algae)

**CAS: 128-37-0 2,6-di-tert-butyl-p-cresol**

LC50 / 96h	>0.57 mg/l (Danio rerio)
EC50 / 48h	>0.17 mg/l (Daphnia magna)
IC50 / 72h	>0.42 mg/l (Desmodemus subspicatus)
NOEC/NOEL	0.39 mg/l (Daphnia magna)

**12.2 Persistence and degradability****Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Biodegradation	69 % (28d)
----------------	------------

(Contd. on page 8)

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2021

Version: 8.00

Revision: 06.08.2019

Trade name: SONAX SX 90 PLUS

(Contd. of page 7)

**CAS: 8042-47-5 White mineral oil, petroleum**

Biodegradation >60 % (28d (OECD 301B))

### 12.3 Bioaccumulative potential

**CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)**

BCF 3.16

log POW >6.6 log POW

**CAS: 128-37-0 2,6-di-tert-butyl-p-cresol**

log POW 5.1 log POW

**12.4 Mobility in soil** No further relevant information available.

### Additional ecological information:

#### General notes:

The product may not be released into the environment without control.

Do not allow product to reach ground water, water course or sewage system.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

**Recommendation** Waste must be disposed of while observing the local, official regulations.

#### European waste catalogue

1) Disposal / product

2) Disposal / contaminated packaging

20 01 13\* solvents

15 01 10\* packaging containing residues of or contaminated by hazardous substances

## SECTION 14: Transport information

### 14.1 UN-Number

ADR, IMDG, IATA

Void

### 14.2 UN proper shipping name

ADR, IMDG, IATA

Void

### 14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class

Void

### 14.4 Packing group

ADR, IMDG, IATA

Void

### 14.5 Environmental hazards:

**Marine pollutant:**

No

### 14.6 Special precautions for user

Not applicable.

### 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code

Not applicable.

UN "Model Regulation":

Void

GB

(Contd. on page 9)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.02.2021

Version: 8.00

Revision: 06.08.2019

Trade name: SONAX SX 90 PLUS

(Contd. of page 8)

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****European Directives:**

EC/1907/2006 (REACH)

EC/1272/2008 (CLP)

EC/648/2004

**National regulations:****Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

**Classification according to Regulation (EC) No 1272/2008**

Serious eye damage/eye irritation  
Aspiration hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Abbreviations and acronyms:**

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Acute Tox. 4: Acute toxicity - inhalation – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**Version history and indication of changes:** Replaces version 7.00.**\* Data compared to the previous version altered.**