



# DVGW type examination certificate

## DVGW-Baumusterprüfzertifikat

**DG-4550CQ0520**  
Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	RubINETTERIE Bresciane Bonomi S.p.A. Via Massimo Bonomi, 1, I-25064 Gussago (Brescia)
<b>Distributor</b> <i>Vertreiber</i>	RubINETTERIE Bresciane Bonomi S.p.A. Via Massimo Bonomi, 1, I-25064 Gussago (Brescia)
<b>Product Category</b> <i>Produktart</i>	Pipe equipment and fittings: Compression joint for metallic gas pipes (4550)
<b>Product description</b> <i>Produktbezeichnung</i>	Press connectors made of bronze or copper for copper pipes (hard and semi-hard) according to DVGW GW 392 (hard and semi hard), unpressed leaky
<b>Model</b> <i>Modell</i>	FRABOPRESS KOMBI
<b>Test reports</b> <i>Prüfberichte</i>	Supplement test: V666/24.A from 11.07.2025 (IMA) Laboratory control test: V261/25.8-1 from 05.08.2025 (IMA) Type testing: B15/10/2034 from 26.01.2015 (DBI)
<b>Test basis</b> <i>Prüfgrundlagen</i>	DVGW G 5614 (01.12.2013) DIN EN 1254-20 (01.10.2021)



**Date of Expiry / File No.** 26.10.2030 / 24-0647-GNV  
*Ablaufdatum / Aktenzeichen*

70028-04-A-DE

18.12.2025 Pz A-1/2

*J. A. W. W.*

Date, Issued by, Sheet, Head of Certification Body  
*Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle*



DVGW CERT GmbH  
Josef-Wirmer-Str. 1-3  
53123 Bonn  
Tel. +49 228 9188-888  
info@dvwg-cert.com  
www.dvbw-cert.com

<b>Gas Category</b> <i>Gasart</i>	<b>Remarks</b> <i>Bemerkungen</i>
Fuel gases acc. to G 260 excl. 5. family	

<b>Type</b> <i>Typ</i>	<b>Technical Data</b> <i>Technische Daten</i>	<b>Remarks</b> <i>Bemerkungen</i>
FRABOPRESS KOMBI	Nominal pressure rating: PN 5/GT-PN 1 Nominal diameter: DN 12	
FRABOPRESS KOMBI	Nominal pressure rating: PN 5/GT-PN 1 Nominal diameter: DN 15	
FRABOPRESS KOMBI	Nominal pressure rating: PN 5/GT-PN 1 Nominal diameter: DN 18	
FRABOPRESS KOMBI	Nominal pressure rating: PN 5/GT-PN 1 Nominal diameter: DN 22	
FRABOPRESS KOMBI	Nominal pressure rating: PN 5/GT-PN 1 Nominal diameter: DN 28	
FRABOPRESS KOMBI	Nominal pressure rating: PN 5/GT-PN 1 Nominal diameter: DN 35	
FRABOPRESS KOMBI	Nominal pressure rating: PN 5/GT-PN 1 Nominal diameter: DN 42	
FRABOPRESS KOMBI	Nominal pressure rating: PN 5/GT-PN 1 Nominal diameter: DN 54	

<b>Type Variation</b> <i>Ausführungsvariante</i>	<b>Explanations</b> <i>Erläuterungen</i>
Übergangsstück/Thread adapter	joints made of red brass; DN12, DN15, DN18, DN22, DN28, DN35, DN42 and DN54 mm; Thread Rp... according to DIN EN 10226-1
Muffe/Coupling	joints made of copper; DN12, DN15, DN18, DN22, DN28, DN35, DN42 and DN54 mm
Bogen/Elbow	joints made of copper; DN12, DN15, DN18, DN22, DN28, DN35, DN42 and DN54 mm
Verschraubung/swivel nut	joint made of red brass; DN28 mm

**certified Components**  
*zertifizierte Bauteile / Werkstoffe*

<b>Registr. No.</b> <i>Registrier-Nr.</i>	<b>Component</b> <i>Bauteil (Produktart)</i>	<b>Model/Type</b> <i>Modell/Typ</i>	<b>Manufacturer</b> <i>Hersteller</i>
NG-5112BN0030	Elastomer material for seals in gas appliances	HN 707/HN707	Lopigom S.p.A.
NG-5112BN0160	Elastomer material for seals in gas appliances	01/I70 HNBR/01/I70 HNBR (H-HBR 70 SHORE gelb)	LAV.EL GOMMA S.r.l.

**Hints of Utilization / Remarks**  
*Verwendungshinweise / Bemerkungen*

Certified versions: RS9001, RS9002, RS9040, RS9041, RS9085, RS9086, RS9270, RS9130, RS9131, RS9243, RS9301, RS9240, RS9271, RS8090, RS8092, RS8130, RS8243, RS8244, RS8245, RS8246, RS8270, RS8272, RS8471  
Pipe type: Hard (R290) and semi-hard (R250) copper pipes according to DVGW Worksheet GW 392  
Ambient temperature range: -20...+70 °C  
The operating temperature requirements at -20 °C are also met at -30 °C.  
The requirements for higher thermal resistance are met up to nominal pressure level PN 1 (GT-PN 1).

