



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 27

Pattex Kraftkleber Classic

SDS No. : 738723
V006.0

Revision: 17.02.2026

printing date: 19.02.2026

Replaces version from: 15.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pattex Kraftkleber Classic
UFI: PMP9-YWVA-D20X-T1CQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Contact adhesive

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

Further information is available at Poison Control Centers.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Ethyl acetate

Hydrocarbons, C7-C8, cyclic

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Supplemental information

Contains: rosin May produce an allergic reaction.

Precautionary statement:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P261 Avoid breathing mist/vapours.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/eye protection.

**Precautionary statement:
Disposal**

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

Pregnant women should absolutely avoid inhalation and skin contact.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS No. EC No REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Ethyl acetate 141-78-6 205-500-4 01-2119475103-46	20- < 40 %	Flam. Liq. 2, H225 STOT SE 3, H336 Eye Irrit. 2, H319		EU OEL
Hydrocarbons, C7-C8, cyclic 01-2119486992-20	20- < 40 %	Aquatic Chronic 2, H411 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336	inhalation:ATE = 23,4 mg/l;vapour	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane ----- 01-2119475514-35	10- < 20 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411		
rosin 8050-09-7 232-475-7 01-2119480418-32	0,1- < 1 %	Skin Sens. 1, H317		
zinc oxide 1314-13-2 215-222-5 01-2119463881-32	0,1- < 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
n-Hexane 110-54-3 203-777-6 01-2119480412-44	0,1- < 1 %	Aquatic Chronic 2, H411 Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 1, H372 Skin Irrit. 2, H315 STOT SE 3, H336		SVHC EU OEL
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5 271-867-2 01-2119496062-39	0,1- < 1 %	Repr. 2, H361d Aquatic Chronic 4, H413		

**If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

Causes serious eye irritation.

Vapors may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

Additional information:

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

During processing and drying after adhesion, ventilate well. Avoid all sources of fire such as stoves and ovens. Switch off all electrical devices such as parabolic heaters, hot plates, storage heaters etc. in good time for them to have cooled down before commencing work. Avoid all sparks, including those occurring at electrical switches and devices.

Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.

Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Keep only in original container.

Store in a cool place, max. storage temperature 30°C.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Contact adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethyl acetate 141-78-6 [ETHYL ACETATE]	200	734	Time Weighted Average (TWA):	Indicative	ECLTV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.468	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Ethyl acetate 141-78-6			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Ethyl acetate 141-78-6	200	730	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Zinc oxide 1314-13-2		10	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Zinc oxide 1314-13-2		1,25	Exposure limit(s):	If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Zinc oxide 1314-13-2			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
n-Hexane 110-54-3 [N-HEXANE]	20	72	Time Weighted Average (TWA):	Indicative	ECLTV
n-Hexane 110-54-3	50	180	Exposure limit(s):	8 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
n-Hexane 110-54-3			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Ethyl acetate 141-78-6	aqua (freshwater)		0,24 mg/l				
Ethyl acetate 141-78-6	aqua (marine water)		0,024 mg/l				
Ethyl acetate 141-78-6	aqua (intermittent releases)		1,65 mg/l				
Ethyl acetate 141-78-6	sewage treatment plant (STP)		650 mg/l				
Ethyl acetate 141-78-6	sediment (freshwater)				1,15 mg/kg		
Ethyl acetate 141-78-6	sediment (marine water)				0,115 mg/kg		
Ethyl acetate 141-78-6	Air						no hazard identified
Ethyl acetate 141-78-6	Soil				0,148 mg/kg		
Ethyl acetate 141-78-6	oral				200 mg/kg		
rosin 8050-09-7	aqua (freshwater)		0,002 mg/l				
rosin 8050-09-7	aqua (marine water)		0,0002 mg/l				
rosin 8050-09-7	sediment (freshwater)				0,007 mg/kg		
rosin 8050-09-7	sediment (marine water)				0,001 mg/kg		
rosin 8050-09-7	Soil				0 mg/kg		
rosin 8050-09-7	sewage treatment plant (STP)		1000 mg/l				
rosin 8050-09-7	aqua (intermittent releases)		0,016 mg/l				
zinc oxide 1314-13-2	aqua (freshwater)		14,4 µg/l				
zinc oxide 1314-13-2	aqua (marine water)		7,2 µg/l				
zinc oxide 1314-13-2	sewage treatment plant (STP)		100 µg/l				
zinc oxide 1314-13-2	sediment (freshwater)				146,9 mg/kg		
zinc oxide 1314-13-2	sediment (marine water)				162,2 mg/kg		
zinc oxide 1314-13-2	Soil				83,1 mg/kg		
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	aqua (freshwater)		0,01 mg/l				
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	aqua (marine water)		0,002 mg/l				
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	sewage treatment plant (STP)		100 mg/l				
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	sediment (freshwater)				426,26 mg/kg		
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	sediment (marine water)				85,25 mg/kg		
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	Soil				85,16 mg/kg		

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	oral				1,7 mg/kg		
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	Freshwater - intermittent		0,002 mg/l				
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	Marine water - intermittent		0,002 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - systemic effects		1468 mg/m ³	no hazard identified
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - local effects		1468 mg/m ³	no hazard identified
Ethyl acetate 141-78-6	Workers	dermal	Long term exposure - systemic effects		63 mg/kg	no hazard identified
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - systemic effects		734 mg/m ³	no hazard identified
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - local effects		734 mg/m ³	no hazard identified
Ethyl acetate 141-78-6	General population	Inhalation	Acute/short term exposure - systemic effects		734 mg/m ³	no hazard identified
Ethyl acetate 141-78-6	General population	inhalation	Acute/short term exposure - local effects		734 mg/m ³	no hazard identified
Ethyl acetate 141-78-6	General population	dermal	Long term exposure - systemic effects		37 mg/kg	no hazard identified
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - systemic effects		367 mg/m ³	no hazard identified
Ethyl acetate 141-78-6	General population	oral	Long term exposure - systemic effects		4,5 mg/kg	no hazard identified
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - local effects		367 mg/m ³	no hazard identified
Hydrocarbons, C7-C8, cyclic	Workers	dermal	Long term exposure - systemic effects		773 mg/kg	
Hydrocarbons, C7-C8, cyclic	Workers	Inhalation	Long term exposure - systemic effects		2035 mg/m ³	
Hydrocarbons, C7-C8, cyclic	General population	dermal	Long term exposure - systemic effects		699 mg/kg	
Hydrocarbons, C7-C8, cyclic	General population	Inhalation	Long term exposure - systemic effects		608 mg/m ³	
Hydrocarbons, C7-C8, cyclic	General population	oral	Long term exposure - systemic effects		699 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	Workers	inhalation	Long term exposure - systemic effects		2035 mg/m ³	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	Workers	dermal	Long term exposure - systemic effects		773 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	General population	inhalation	Long term exposure - systemic effects		608 mg/m ³	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	General population	dermal	Long term exposure - systemic effects		699 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	General population	oral	Long term exposure - systemic effects		699 mg/kg	
rosin 8050-09-7	Workers	inhalation	Long term exposure - local effects		10 mg/m ³	
rosin 8050-09-7	Workers	dermal	Long term exposure -		2,131 mg/kg	

			systemic effects			
rosin 8050-09-7	General population	dermal	Long term exposure - systemic effects		1,065 mg/kg	
rosin 8050-09-7	General population	oral	Long term exposure - systemic effects		1,065 mg/kg	
n-Hexane 110-54-3	Workers	inhalation	Long term exposure - systemic effects		75 mg/m3	
n-Hexane 110-54-3	Workers	dermal	Long term exposure - systemic effects		11 mg/kg	
n-Hexane 110-54-3	General population	inhalation	Long term exposure - systemic effects		16 mg/m3	
n-Hexane 110-54-3	General population	dermal	Long term exposure - systemic effects		5,3 mg/kg	
n-Hexane 110-54-3	General population	oral	Long term exposure - systemic effects		4 mg/kg	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	Workers	dermal	Long term exposure - systemic effects		0,42 mg/kg	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	Workers	inhalation	Long term exposure - systemic effects		0,29 mg/m3	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	General population	dermal	Long term exposure - systemic effects		0,21 mg/kg	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	General population	inhalation	Long term exposure - systemic effects		0,07 mg/m3	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	General population	oral	Long term exposure - systemic effects		0,04 mg/kg	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
n-Hexane 110-54-3	Hexane-2,5-dione plus 4,5-Dihydroxy-2-hexanone (with hydrolysis)	Urine	Sampling time: End of shift.	5 mg/l	DE BGW		

8.2. Exposure controls:

Respiratory protection:
Suitable breathing mask when there is inadequate ventilation.
Combination filter: ABEKP (EN 14387)
This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

material thickness > 0.4 mm

Perforation time > 10 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	liquid
Colour	Beige
Odor	Typical
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	-7 °C (19.4 °F)
Initial boiling point	75 °C (167 °F)
Flammability	Highly flammable.
Explosive limits	
lower	2,00 %(V);
upper	11,50 %(V);
	Value of most critical component
Flash point	-14,5 °C (5.9 °F); DIN 51755 Closed cup flash point
Auto-ignition temperature	430,0 °C (806 °F) Value of most critical component
Decomposition temperature	Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-polar/aprotic.
Viscosity (kinematic) (40 °C (104 °F);)	1.600 - 2.100 mm ² /s
Viscosity, dynamic (; 20 °C (68 °F))	1.500 - 2.000 mPa.s TE1002-208; Viscosity by Brookfield
Viscosity, dynamic (; 40 °C (104 °F))	1.300 - 1.700 mPa.s
Solubility (qualitative) (Solvent: Water)	Not miscible
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure	Mixture 98,0000000 mbar Value of most critical component
Density (20 °C (68 °F))	0,84 - 0,88 g/cm ³ QP2107.1; Density
Density (40 °C (104 °F))	0,79 - 0,82 g/cm ³
Relative vapour density:	Heavier than air
Particle characteristics	Not applicable

Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethyl acetate 141-78-6	LD50	6.100 mg/kg	rat	not specified
Hydrocarbons, C7-C8, cyclic	LD50	> 5.840 mg/kg	rat	not specified
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane -----	LD50	> 5.840 mg/kg	rat	not specified
rosin 8050-09-7	LD50	2.800 mg/kg	rat	not specified
zinc oxide 1314-13-2	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
n-Hexane 110-54-3	LD50	16.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethyl acetate 141-78-6	LD50	> 20.000 mg/kg	rabbit	Draize Test
Hydrocarbons, C7-C8, cyclic	LD50	> 2.800 mg/kg	rat	not specified
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane -----	LD50	> 2.800 mg/kg	rat	not specified
rosin 8050-09-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
zinc oxide 1314-13-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
n-Hexane 110-54-3	LD50	> 2.000 mg/kg	rabbit	not specified
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The toxicity of the product is due to its narcotic effect after inhalation.
In the event of protracted or repeated exposure, damage to health cannot be excluded.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Ethyl acetate 141-78-6	LC50	57,7 mg/l	vapour	4 h	rat	not specified
Ethyl acetate 141-78-6	LC50	> 22,5 mg/l	vapour	6 h	rat	other guideline:
Hydrocarbons, C7-C8, cyclic	LC50	> 23,3 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C7-C8, cyclic	Acute toxicity estimate (ATE)	23,4 mg/l	vapour	4 h		Expert judgement
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane -----	LC50	> 25,2 mg/l	vapour	4 h	rat	not specified
zinc oxide 1314-13-2	LC50	> 5,7 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
n-Hexane 110-54-3	LC50	> 31,86 mg/l	vapour	4 h	rat	not specified
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	LC50	> 165 mg/l	dust/mist	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethyl acetate 141-78-6	slightly irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane -----	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
rosin 8050-09-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
n-Hexane 110-54-3	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	not irritating	4 h	rabbit	EPA Guideline

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethyl acetate 141-78-6	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hydrocarbons, C7-C8, cyclic	not irritating		rabbit	FDA Guideline
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane -----	not irritating		rabbit	FDA Guideline
rosin 8050-09-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
n-Hexane 110-54-3	not irritating		rabbit	not specified
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	slightly irritating	24 h	rabbit	EPA Guideline

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Ethyl acetate 141-78-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
zinc oxide 1314-13-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
n-Hexane 110-54-3	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethyl acetate 141-78-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethyl acetate 141-78-6	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
rosin 8050-09-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
rosin 8050-09-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
rosin 8050-09-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
zinc oxide 1314-13-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
zinc oxide 1314-13-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
zinc oxide 1314-13-2	ambiguous	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
n-Hexane 110-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
n-Hexane 110-54-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Ethyl acetate 141-78-6	negative	oral: gavage		hamster, Chinese	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
zinc oxide 1314-13-2	negative	inhalation: aerosol		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
zinc oxide 1314-13-2	negative	inhalation: aerosol		rat	OECD Guideline 489 (In Vivo Mammalian Alkaline Comet Assay)
n-Hexane 110-54-3	negative	inhalation: vapour		mouse	not specified
n-Hexane 110-54-3	negative	inhalation: vapour		rat	not specified

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
zinc oxide 1314-13-2	not carcinogenic	oral: drinking water	1 y daily	mouse	male/female	not specified
n-Hexane 110-54-3	not carcinogenic	inhalation: vapour	2 y 6 h/d; 5 d/w	mouse	female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Ethyl acetate 141-78-6	NOAEL P 1500 ppm	other:	inhalation	rat	other guideline:
rosin 8050-09-7	NOAEL P 3000 ppm NOAEL F1 3000 ppm	screening	oral: feed	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
zinc oxide 1314-13-2	NOAEL P 7,5 mg/kg NOAEL F1 15 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
n-Hexane 110-54-3	NOAEL P 9000 ppm NOAEL F1 3000 ppm NOAEL F2 3000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Ethyl acetate 141-78-6	May cause drowsiness or dizziness.			
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane -----	Category 3 with narcotic effects.			
n-Hexane 110-54-3	May cause drowsiness or dizziness.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Ethyl acetate 141-78-6	NOAEL 900 mg/kg	oral: gavage	90 d daily	rat	EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
rosin 8050-09-7	NOAEL 5000 ppm	oral: feed	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
zinc oxide 1314-13-2	NOAEL 31,52 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
zinc oxide 1314-13-2	NOAEL 1.5 mg/m ³	inhalation	3 m 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
zinc oxide 1314-13-2	NOAEL 1.000 mg/kg	dermal	90 d 6 h/d, daily	rat	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
n-Hexane 110-54-3	NOAEL 40 mg/kg	oral: gavage	13 weeks daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
n-Hexane 110-54-3	NOAEL 13,2 mg/kg	oral: gavage	90-120 d 5 d / week	rat	not specified
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	NOAEL 500 ppm	oral: feed	90 Days Daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane -----	0,61 mm ² /s	25 °C	not specified	
n-Hexane 110-54-3	0,45 mm ² /s	25 °C	not specified	

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

No data available.

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains, soil or bodies of water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	LC50	220 mg/l	96 h	Pimephales promelas	other guideline:
Hydrocarbons, C7-C8, cyclic	LL50	3,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	LL50	11,4 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
rosin 8050-09-7	LC50	Toxicity > Water solubility	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	LC50	0,142 mg/l	96 h	Thymallus arcticus	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	NOEC	0,44 mg/l	72 d	Oncorhynchus mykiss	other guideline:
n-Hexane 110-54-3	LC50	> 1 - 10 mg/l	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	LC50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	NOELR	Toxicity > Water solubility	34 d	Pimephales promelas	OECD Guideline 210 (fish early life stage toxicity test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	EC50	164 mg/l	48 h	Daphnia cucullata	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C7-C8, cyclic	EL50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	EL50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
rosin 8050-09-7	EL50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
zinc oxide 1314-13-2	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
n-Hexane 110-54-3	EC50	2,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
---	------	-----------------------------	------	---------------	--

Chronic toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	NOEC	2,4 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C7-C8, cyclic	NOELR	1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	NOEC	0,17 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
zinc oxide 1314-13-2	NOEC	0,058 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	NOELR	Toxicity > Water solubility	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	EC50	> 2.000 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl acetate 141-78-6	NOEC	2.000 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C7-C8, cyclic	EL50	29 mg/l	96 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C7-C8, cyclic	NOELR	6,3 mg/l	96 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane -----	EL50	> 30 - 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane -----	NOELR	3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	EL50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	NOELR	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	NOEC	0,017 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	EC50	0,17 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
n-Hexane 110-54-3	EC50	> 1 - 10 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	NOEC	Toxicity > Water solubility	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	EC50	Toxicity > Water solubility	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	EC10	2.900 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
rosin 8050-09-7	EC20	Toxicity > Water solubility	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
zinc oxide 1314-13-2	IC50	5,2 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
n-Hexane 110-54-3	EC50	> 1 - 10 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability**Biodegradability (Screening Tests):**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Ethyl acetate 141-78-6	readily biodegradable	aerobic	100 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydrocarbons, C7-C8, cyclic	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -----	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
rosin 8050-09-7	readily biodegradable	aerobic	71 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
n-Hexane 110-54-3	readily biodegradable	aerobic	81 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	not inherently biodegradable	aerobic	1 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)

(Bio)degradability (Simulation Tests):

No data available.

12.3. Bioaccumulative potential**Partition Coefficient (octanol/water)**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Ethyl acetate 141-78-6	0,68	25 °C	EPA OPPTS 830.7560 (Partition Coefficient, n-octanol / H ₂ O, Generator Column Method)
rosin 8050-09-7	> 3 - 6,2		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
n-Hexane 110-54-3	4	20 °C	other guideline:
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	7,56	30 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

Bioconcentration factor (BCF)

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Ethyl acetate 141-78-6	30	3 d	22,5 °C	Leuciscus idus melanotus	other guideline:
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	2.588,2				OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

No data available.

12.5. Results of PBT / vPvB / PMT / vPvM assessment

PBT/vPvB

The following table contains only substances that fulfill the criteria as PBT and/or vPvB.

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT	vPvB
zinc oxide 1314-13-2	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.	

PMT/vPvM

This mixture does not contain any substances that are assessed to be a PMT or vPvM.

Based on available data, the classification criteria are not met.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080409

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1133
RID	1133
ADN	1133
IMDG	1133
IATA	1133

14.2. UN proper shipping name

ADR	ADHESIVES
RID	ADHESIVES
ADN	ADHESIVES
IMDG	ADHESIVES (Hydrocarbons mixture)
IATA	Adhesives

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

Seveso III (2012/18/EU): E2, Hazardous to the Aquatic Environment in Category Chronic 2
P5c, Flammable liquids, Categories 2 or 3 not covered by P5a and P5b

National regulations/information (Germany):

WGK: WGK 2: significantly water endangering (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

Storage class according to TRGS 510: 3

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H361f Suspected of damaging fertility.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms:

ADG(-Code): Australian Dangerous Goods (Code)
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM: American Society for Testing and Materials
ATE: acute toxicity estimate
AS: Australian Standard
AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water
CAS: Chemical Abstract Service
CLP: Regulation (EC) No 1272/2008
CMR: cancerogenic, mutagenic or reprotoxic
DIN: German Institute for Standardization
ECx: Effective concentration (x% effective level)
ECHA: European Chemicals Agency
EC-Nummer: Substance number in the EU-inventories EINECS/ELINCS
ECTLV: European community threshold limit value
ED: Substance identified as having endocrine disrupting properties
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EN : European Standard
ENCS: Japanese chemical inventory
EPA: US Environmental Protection Agency
EU: European Union
EU EXPLD1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD2: Substance listed in Annex II, Reg (EC) No. 2019/1148
EWC: European Waste Catalogue
GHS: Globally Harmonised System for Classification and Labelling of Chemicals
GLP: Good Laboratory Practice
HSNO: Hazardous Substances and New Organisms
IARC: International Agency for Research of Cancer
IATA: International Air Transport Association
IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization
IMDG-Code: International Maritime Code for Dangerous Goods
IMO: International Maritime Organization
ISO: International Standardization Organisation
LC50: Median lethal concentration
LD50: Median lethal dose
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
n.o.s.: not otherwise specified
NO(A)EC: No (adverse) effect concentration
NO(A)EL: No (adverse) effect level
NZS: New Zealand Standard
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit

OPPT: US EPA Office of Pollution Prevention and Toxics
OPPTS: US EPA Office of Prevention, Pesticides and Toxic Substances
PBT: Persistent, bioaccumulative, toxic
PMT: Persistent, mobile and toxic
(Q)SAR: (Quantitative) structure–activity relationship
REACH: Regulation (EC) No. 1907/2006
RID: Regulations concerning the International Transport of Dangerous Goods by Rail
SADT: Self Accelerating Decomposition Temperature
SDS: Safety Data Sheet
STOT: Specific Target Organ Toxicity
STOT SE: Specific Target Organ Toxicity - single exposure
STOT RE: Specific Target Organ Toxicity - repeated exposure
SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons
SVHC: Substance of very high concern (REACH Candidate List)
TRGS: German Technical Rules for hazardous substances
UN: United Nations
VOC: Volatile Organic Compound
814.018 VOC Reg CH: Swiss Ordinance 814.018 on the Incentive Tax on Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative
vPvM: Very persistent and very mobile
VwVwS: Administrative Regulation on Substances Hazardous to Waters
WGK: Water hazard class

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.